COSHH ASSESSMENT CONCRETE ROOF TILES

Product Name(s):	Concrete Roof Tiles				COSHH Assess. N	No.:	•	11
Description of Substance:	Pre cast cor	ncrete roof t	iles		Assessed	d By:		
Workplace Exposure Limits:	inhalable Ca TWA)	alcium Silica	ite dust 10m	ng/m³ (8hr	Date:			
Task/Activity:	Cutting concrete roof tiles							
Suppliers Name					Telephon Fax No's:			
& Address:					MSDS Attached	:	Yes / N	No
		SUBS	STANCE PR	OPERTIES				
						*	J.J.	L.Un
Flammable/ Highly Flammable	Oxidiser	Explosive	Harmful	Toxic/ Very Toxic	Irritant	t	erous to he onment	Corrosive
No	No	No	Yes	No	Yes	1	No	No

ROUTE OF EXPOSURE						
Skin		Eyes	Х	Inhalation	х	
Ingestion	X	Cuts/ Abrasions		Injection		

PERSONS AT RISK					
Users of the product	X	Members of Public		Visitors	
Other Workers	X	Young Persons			

	PPE REQUIREMENTS						
						M	0
Yes	Yes	Yes FFP3	No	Yes	No	Optional	Other

ADDITIONAL CONTROL MEASURES				
General Precautions	Control Measures			
Ensure that the above specified PPE is worn and that all staff are informed of the risks; control measures and precautions required when working with the substance.	Ensure that adequate supervision is provided at all times.			

COSHH ASSESSMENT CONCRETE ROOF TILES

First Aid/Hygiene Arrangements	Fire Precautions
 Wash skin thoroughly with soap and clean water If contact is made with the eye, immediately flood the eye with plenty of clean water for at least 10 minutes and seek immediate medical attention. If inhalation or ingestion occurs, seek immediate medical attention. Wash out the mouth with clean water where appropriate. 	>

LEV Requirements			Monitoring Requirements			
A	Ensure that the work area is well ventilated at all times. Avoid inhalation of dust generated by the process.	AA	Consider additional monitoring if this product is to be used within a confined space. Provide additional monitoring where young or inexperienced workers are carrying out the works.			

Transport Arrangements	Storage Requirements			
No special requirements for small quantities	Store in a dry, well ventilated and secure store.Protect from extremes of temperature.			

S	pillage Procedures	Disposal Requirements			
A A	Spillages should be cleaned up using a brush and shovel, whilst avoiding excessive dust creation. The material should then be placed into a suitable container for disposal.	Dispose of waste containers etc as normal builders waste via a licensed waste contractor.			

Comments

This is only a preliminary assessment based on generic information for similar products.

This assessment must be reviewed and amended by a competent person prior to its contents being used. This is to ensure that consideration is given to site specific circumstances or differences which may affect the original assessment. It is the employers responsibility to ensure that a suitable and sufficient assessment of the risks is undertaken when using any material which may be hazardous to health.

An up to date Material Safety Data Sheet (MSDS) should be obtained from the supplier and reviewed alongside this assessment to ensure that the control measures are suitable and remain valid.