COSHH ASSESSMENT ROCKWOOL INSULATION

Product Name(s):	Rockwo	Rockwool Insulation			COSHH Assess.	No.:	•	30
Description of Substance:		Friable fibrous material used for its sound and thermal insulation properties.				d By:		
Workplace Exposure Limit	s: Man Ma	Man Made Mineral Fibres 5mg/m³			Date:			
Task/Activity:	Unrollin	Unrolling and placement of insulation between ceiling joists.						
Suppliers Name	9				Telephor Fax No's			
& Address:					MSDS Attached	:	Yes / N	lo
SUBSTANCE PROPERTIES								
			X _n		X	*		L.U
Flammable/ Highly Flammable	Oxidiser	Explosive	Harmful	Toxic/ Very Toxic	Irritant	t	erous to the onment	Corrosive
No	No	No	No	No	Yes	1	Vo	No

	ROUTE OF EXPOSURE					
Skin	х	Eyes		Inhalation	X	
Ingestion		Cuts/ Abrasions		Injection		

PERSONS AT RISK					
Users of the product	х	Members of Public	X	Visitors	X
Other Workers	X	Young Persons	X		

PPE REQUIREMENTS							
						Other:	Other:
Yes	Yes	Yes FFP3	No	Yes	No	Yes / No	Yes / No

	ADDITIONAL CONTROL MEASURES					
General Precautions		ontrol Measu	ıres			
A	Ensure that the above specified PPE is worn and that all staff are informed of the risks; control measures and precautions required when working with the substance.	Ensure that times.	t adequate supervision is provided at all			

COSHH ASSESSMENT ROCKWOOL INSULATION

First Aid/Hygiene Arrangements	Fire Precautions
 Wash skin thoroughly with soap and clean water If contact is made with the eye, immediately flood the eye with plenty of clean water for at least 10 minutes and seek immediate medical attention. If inhalation or ingestion occurs, seek immediate medical attention. Wash out the mouth with clean water where appropriate. 	

LEV Requirements	Monitoring Requirements		
Ensure that the work area is well ventilated at all times.	 Consider additional monitoring if this product is to be used within a confined space. Provide additional monitoring where young or inexperienced workers are carrying out the works. 		

Transport Arrangements	Storage Requirements			
No special requirements for small quantities	 Store in a dry, well ventilated and secure store. Protect from extremes of temperature. 			

Spillage Procedures	Disposal Requirements
	Dispose of waste normal builders waste.

Comments

This is only a preliminary assessment based on generic information for similar products.

This assessment must be reviewed and amended by a competent person prior to its contents being used. This is to ensure that consideration is given to site specific circumstances or differences which may affect the original assessment. It is the employers responsibility to ensure that a suitable and sufficient assessment of the risks is undertaken when using any material which may be hazardous to health.

An up to date Material Safety Data Sheet (MSDS) should be obtained from the supplier and reviewed alongside this assessment to ensure that the control measures are suitable and remain valid.